

Compact and convenient, with all the features you need for field work.

Caplio
500SE
model W / model B

Camera shake blur reduction

Caplio 500G wide effectively reduces camera shake blur by combining high ISO settings with fast shutter speeds. Now you can shoot with greater confidence in dark situation

Powerful built-in flash

The built-in flash unit allows clearer shooting in a wider range of situations. Its powerful illumination extends 10 meters in wide-angle shots and 6.5 meters in telephoto shots

Large, easy-to-view 2.5-inch LCD screen

The large LCD screen features an anti-reflection coating for clearer viewing in daylight outdoors. You can easily adjust screen brightness to optimize image clarity. There is also an optical viewfinder, so you can use whichever is right for the situation, for more reliable photography.



Wide coverage with 28mm wide-angle zoom lens

Ricoh's 28mm wide-angle zoom lens can capture larger areas than the 35mm lenses of conventional digital cameras. When there is limited space to maneuver, you can more easily capture an entire building or construction site with Caplio 500SE

Vivid 1cm macro photography

Capture subjects as close as 1cm away in the macro wide-angle mode or 10cm away in the tele-macro mode. The built-in flash unit illuminates subjects as close as 20cm from the camera

Large buttons and dials

All buttons and dials are large enough to ensure you can easily operate the camera even when wearing gloves



Memo function for more convenient data management

Keep memos as part of your photo information. Memos are particularly handy for distinguishing numerous similar photographs and can dramatically heighten management efficiency

Barcode memo function for temporary memos (model W only)

Shoot one-dimensional barcodes with the Caplio 500SE and register the barcode photos as temporary memos

Caplio 500SE Major Specifications

Item	Description
CCD	Effective 8.13 million pixels (8.30 million square pixels), 1/1.8-inch primary-color CCD
Lens	Focal length f: 5.8-17.4mm (equivalent to 28-85mm for 35mm film cameras) Step-zoom intervals: 4 steps (28mm, 35mm, 50mm, 85mm) Aperture F: 2.5 (W)-4.3 (T)
Recording Media	SD Memory Card™ (3.3V 32/64/128/256/512MB/1GB), Multi Media Card™, Built-in Memory 26MB
Recording Mode	Still mode (Continuous, S-Continuous, M-Continuous), Scene mode (High-sensitivity, Fire, Skew Correction, Text, Zoom Macro), Motion mode, Sound mode
LCD Monitor	2.5" translucent amorphous silicon TFT LCD (approx. 153,000 pixels)
Dimensions (WxDxH)	133.0 x 78.5 x 74.0mm (excluding projections)
Weight	Approx. 430g (excluding battery, SD Memory Card, hand strap) Accessories (battery, hand strap) approx. 50g
Power Source	Rechargeable battery (DB-43) x 1, AA battery x 2, AC adaptor (AC-4d)
Bluetooth® specifications	Communication scheme: Bluetooth® standard version 2.0+EDR Output: Bluetooth® standard Power Class 2 Supported Bluetooth® profiles: BIP, OPP, SPP
Wireless LAN specifications (model W only)	Interface standard: IEEE802.11b/g Security: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES)

Caplio 500SE Optional Accessories

Accessory Name	
Wide conversion lens: DW-5	Battery Charger: BJ-2e
Rechargeable Lithium-Ion Battery Set (DB-43+BJ-2e): BS-3e	AC Adapter: AC-4d
Rechargeable Lithium-Ion Battery: DB-43	Soft Case: SC-500

• The Bluetooth® word mark and logo are registered trademarks of Bluetooth SIG, Inc. Bluetooth® technology is used by Ricoh Co., Ltd. under licensing agreement with Bluetooth SIG, Inc. • Caplio is the registered trademark of Ricoh Co., Ltd. • Microsoft, Windows and Direct X are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. • Apple, Macintosh and Mac OS are registered trademarks or trademarks of Apple Computer Inc. in the U.S. and/or other countries. • The SD logo is a trademark. • Compatible with EPSON PRINT Image Matching III. • All other trademarks mentioned herein are the property of their respective owners.



DuraTechUSA Inc.

6765 Westminster Ave #314

Westminster, CA 92683

Tel: 714-898-2171 Fax: 866-704-9132

Email: sales@DuraTechUSA.com

www.DuraTechUSA.com

RICOH

RICOH COMPANY, LTD.

3-2-3, Shin-yokohama
Kohoku-ku, Yokohama-shi 222-8530, Japan
Phone: 045-477-1738 Fax: 045-477-1797 http://www.ricoh.com/r_dc

RICOH EUROPE B.V. (PMMC EUROPE)

Oberrather Straße 6, D-40472
Düsseldorf, Germany
Phone: 0211-6546-0 Fax: 0211-6546-308 <http://www.ricohpmmc.com>

RICOH UK LTD. (PMMC UK)

Ricoh House, 1 Plane Tree Crescent, Feltham,
Middlesex, TW13 7HG, England
Phone: 0208-261-4000 Fax: 0208-261-4220

RICOH FRANCE S.A. (PMMC FRANCE)

383, Avenue du Général de Gaulle – BP 307-931-13
Clamart Cédex, France
Phone: 01-4 949 3267 Fax: 01-4094-3276

RICOH ESPANA, S.A. (PMMC SPAIN)

Av. Litoral Mar, 12-14, 08005
Barcelona, Spain
Phone: 093-295-7600 Fax: 093-295-7605

RICOH ITALIA S.p.A. (PMMC ITALY)

via Ponchielli, 3
20063 Cernusco S/N Milano, Italy
Phone: +39-02-92361217 Fax: +39-02-92361244

RICOH HONG KONG LIMITED

Personal Multimedia Products Center
21/F., Tai Yau Building, 181 Johnston Road, Wan Chai, Hong Kong
Phone: 2862-2888 Fax: 2566-3647/2866-1120

RICOH AUSTRALIA PTY. LTD.

8 Rodborough Road, Frenchs Forest, N.S.W. 2086 Australia
Phone: 02-8977-1111 Fax: 02-8977-1100
<http://www.ricoh.com.au>

RICOH CORPORATION

5 Dedrick Place
West Caldwell, NJ 07006 U.S.A.
Phone: 1-800-Ricoh93 <http://www.ricoh-usa.com>