

LX

Marine Touch Monitors

DuraTech USA, Inc.
 6765 Westminster Ave #314 Westminster, CA 92683
 Call : (714) 898-2171 Fax: 866-704-9132
www.DuraTechUSA.com sales@DuraTechUSA.com



SPECIFICATIONS	NEW! LX0850PTI - 8.4"	NEW! LX1201PTI - 12"	NEW! LX1501PTI - 15"
Part Numbers	997-4387-00LF	997-4350-00LF	997-5422-00LF
Native Resolution	SVGA	XGA	XGA
Touchscreen Type	Infrared (IR)	Infrared (IR)	Infrared (IR), 4096 points of resolution
Touchscreen Interface	USB	USB	USB
Brightness (typical)	>700 cd/m ²	>800 cd/m ²	1200 Nits
Contrast Ratio (typical)	600:1	600:1	650:1
Viewing Angle (typical)	160° H, 140° V	130° H, 115° V	80° H, 70° V
Power Consumption (typical)	<15 W	<30 W	<45 W
Supply Voltage	8 - 32 VDC	8 - 32 VDC	8 - 32 VDC
Video Interface	Analog, VGA	Analog, VGA	Analog, VGA
External Connections	D-Sub 15-pin, Video Connector USB Type B, Locking Connector 7-pin, Locking Power Connector	D-Sub 15-pin, Video Connector USB Type B, Locking Connector 7-pin, Locking Power Connector	Waterproof D-sub 15-pin, Video Connector, Waterproof USB Type B Locking Connector, Waterproof Locking Power Connector
Features	IP65 Waterproof Enclosure	IP65 Waterproof Enclosure	IP65 Waterproof Enclosure
Dimension (WxHxD)	220 mm x 187 mm x 54 mm	315 mm x 251 mm x 69 mm	315 mm x 251 mm x 69 mm
Weight	3.0 kg (6.6 lbs.)	3.7 kg (8.2 lbs.)	3.7 kg (8.2 lbs.)
Approvals	FCC Class A, CE, UL, TUV	FCC Class A, CE, UL, TUV	FCC Class A, CE, UL, TUV
Operating Temperature	-20 to +60 °C (-4 to 140 °F)	-20 to +60 °C (-4 to 140 °F)	-20 to +70 °C (-4 to 158 °F)
Storage Temperature	-20 to +85 °C (-4 to 185 °F)	-20 to +70 °C (-4 to 158 °F)	-20 to +80 °C (-4 to 176 °F)
Service and Support	1 Year standard return to depot, Bronze and Silver Service available (p/n 990-0213-00) optional	1 Year standard return to depot, Bronze and Silver Service available (p/n 990-0213-00) optional	1 Year standard return to depot, Bronze and Silver Service available (p/n 990-0213-00) optional



Front

Back