

Fully Rugged Tablet PC

RT10A

RT10D

Tough Features

Drop Resistance	26 drops of 36 inches height to 0.7" plywood over concrete with unit off Mil Std 810G-516.6, Procedure IV
Spill Resistance	Meets Mil Std 810G-506.5, Procedure II, (Unit is not operating IPX5)
Shock Resistance	Mil Std 810G-514.6, Procedure I Cat. 24, Fig.514.6 E-1 & 514.6E-2 (unit is non operating) ASTM 4169-99 Truck Assurance Level II, Schedule E (Unit is operating)
Dust Resistance	Meet IEC 60529 IP-6X standard, No ingress of dust : complete protection against contact

System Specifications

*Processor	Intel® Atom N270 1.6GHz Processor	Intel® Core Duo U2500 ULV 1.2GHz
System Memory	200-pin DDRII SODIMM Socket x 1, up to 2GB (Factory Option)	
Storage	2.5" SATA Hard Disk/SSD	
Display	10.2" WSVGA (1024 x 600) TFT LCD display w/ LED-backlight, Touch Screen panel (AOT) and digitizer Sunlight readable 500 nit	
Chipset	Intel® 945GSE & Intel® ICH7M	Intel® 945GME & Intel® ICH7M
Expansion Slot	PCMCIA, Two Mini Card Slot(internal), CompactFlash Slot	
Operating system	Windows 7, Vista, XP, Embedded Standard 2009	
I/O Ports	<ul style="list-style-type: none">• One RS-232• Two USB 2.0• One Docking port (contact pin with USB/RS-232/VGA/Power signal)• One Mini USB• Two Audio in/out jack for Microphone/ Earphone• DC-In jack• One RJ-45 jack for 10/100/1000Mbps Ethernet• One 15 pin D-sub VGA port for ext. monitor/projector	
Audio	<ul style="list-style-type: none">• High Definition Audio• Internal Microphone	<ul style="list-style-type: none">• Internal speaker
Wireless/Communications	<ul style="list-style-type: none">• Gigabit Ethernet(10/100/1000Mbps)• Bluetooth 2.0 EDR Class 1 Module	<ul style="list-style-type: none">• WLAN 802.11 b/g
Power Supply	<ul style="list-style-type: none">• AC Power input: 100V-240V, 50Hz-60Hz, 65W• 3S3P 9cells Smart Li-Ion (7,800 mAh), 6 Hrs Battery Life	<ul style="list-style-type: none">• DC Power output: 20V
Temperature	<ul style="list-style-type: none">• Operating Temperature: -4°F ~ 140°F (-20°C ~ 60°C) with HDD heater• Storage Temperature: -67°F ~ 167°F (-55°C ~ 75°C)	
Humidity	10 to 95% @ 104°F(40°C), non-condensing	
Security	Fingerprint Recognition(option), TPM1.2 Optional Smart Card reader(Substitute for PCMCIA slot)	
Dimensions & Weight	270mm(W) x 184mm(D) x 49mm(H) / 10.63"(W) x 7.24"(D) x 1.93"(H) Approximately 2.3Kg / 5lbs(with 9 cell battery, hand strap & bumpers)	
Certification	CE / FCC Class B / UL	

Docking Station(Optional)

Mounting Interface	Wall mount VESA 75 & 100 compatible
I/O	<ul style="list-style-type: none">• Four USB 2.0• One RJ-45 jack for 10/100Mbps Ethernet• One 9 pin D-sub Serial port• One 15 pin D-sub VGA port• One Multi-IO port(contact pin with USB/RS232/VGA//Power signal)
Color	Black



DuraTech USA Inc.
A Certified 8(a), SDB, DBE, SBE, MBE, WBE firm.
Phone: (714) 898-2171 Fax: 866-704-9132
Email: sales@DuraTechUSA.com www.DuraTechUSA.com