

Rugged Tablet PC's and Ultra-Mobile Notebooks



Model Name	Duo-Touch® II Tablet PC	GoBook® MR-1
Rugged Classification	Rugged 'Slate' Tablet PC (Die-Cast Magnesium)	Rugged, Ultra-Mobile Notebook (Die-Cast Magnesium)
Dimensions / Weight	10.6" (L) x 1.65" (D) x 7.2" (W) / 4.1 lbs (1.86 kg)	1.56" (H) x 6.0" (W) x 4.33" (D) / 2.0 lbs (.91 kg) with standard battery
Rugged Specifications	Meets or exceeds MIL STD 810F; IP54 Rating; Sealed I/O Ports; Optional Compliance UL1604 Class 1, Division 2, Group A, B, C and D for Hazardous Location	Meets or exceeds MIL STD 810F; IP54 Rating; Sealed I/O Ports; Optional Compliance UL1604 Class 1, Division 2, Group A, B, C and D for Hazardous Location
Processor	Intel® Core™ Duo ULV, 1.2GHz U2500	Intel® Core™ Solo ULV, 1.2GHz U1400, 533 FSB, 2 MB L2 Cache
Mounting Options	Vehicle Dock and Desk Mount with Communications Ports	Vehicle Dock; Expanded IO box; Mini Office Dock
Display	8.4" SVGA TFT Transmissive outdoor viewable display with award winning DynaVue™ patent-pending technology, User adjustable backlit display to 25 steps	5.6" WSVGA TFT Transmissive outdoor viewable display with award winning DynaVue™ patent-pending technology, User adjustable backlit display to 64 steps
Touchscreen	Std. Active (digitizer pen required) 2540 PP and Passive touchscreen	Integrated touchscreen, Passive touchscreen option
Hard Disk Drive (HDD) or CompactFlash	Shock mounted 2.5" 60GB or 120GB HDD with heater, Optional 16GB or 32GB Solid State Drive	Shock mounted 1.8" PATA 40GB or 80GB with HDD heater, Optional 16GB or 32GB Solid State Drive
Operating system	Microsoft® Windows XP® Tablet PC Edition 2005 or Windows® Vista®	Microsoft® Windows XP® or Windows® VISTA®
Memory Available (std. and max.)	512MB to 2GB DDRII SDRAM	512MB or 1GB DDRII DDRAM
Available Drives	PC Card type I or II, CompactFlash type I or II	N/A
I/O Ports	RJ-11; (2) USB; 26-Pin docking; audio; RJ-45 for 10/100/1000 Mbps Ethernet LAN	1 USB and Docking Connector, Optional Expansion Module with 1 RS 232 and 1 USB
Keyboard	Virtual Keyboard; External USB Keyboard option	76-key sealed, backlit keyboard. Dedicated right and left mouse click keys
Power supply	3900mAH LI-ion (main), 3900mAH LI-Ion (expansion), 12V and 24V vehicle adapter, 90W power adapter	4000 mAH (29Wh) Lithium Polymer main battery Optional 8000 mAH (59Wh) Lithium ION 'extended' battery pack Battery Gas Gauge
Battery life (w/o radios)	3 hrs (main); 6 hrs (main + expansion)	3 hours (main); 6 hours (extended)
Modem	56kbps V.92	N/A
Integrated Wireless	Support for simultaneous WWAN, 802.11 a/g/n, Bluetooth®, User accessible PCMCIA bay for PC Card WWAN radios	Support for simultaneous WWAN, 802.11 a/b/g and Bluetooth®; WWAN options include 1xRTT/EVDO rev. A or EDGE/UMTS/HSDPA
Warranty	3 yr Limited Warranty, Expanded service option: Ruby/Emerald and Diamond	3 yr Limited Warranty, Expanded service option: Sapphire, SapphirePlus
Accessories	Vehicle Power adapter; Hand strap; Port replicator; Carry cases; Shoulder straps; Expansion (secondary) battery	Mini Office Dock; Vehicle Dock
Operating Temperature	Operating temperature: -20° to +60° C (-4° to +140° F)	Operating temperature -20° to +60° C (-4° to +140° F)
Security	Password Security; Cable lock slot; Trusted platform module (TPM) security chip v.1.2; Fingerprint scanner (optional); SmartCard reader (optional)	Password Security; Cable lock slot; Trusted platform module (TPM) security chip v.1.2; Fingerprint scanner (optional); SmartCard reader (optional)